

# Fagor EVO-CONCEPT glass washer with drain pump and detergent & rinse dispenser cold rinse - CO-402BDD

## Quick Overview

- Front loading glasswasher - EVO Generation - Advanced range.
- Basket size: 400 x 400 mm.
- Hourly production: 40 baskets/hour.
- Clearance (max ware height): 275 mm.
- Valid for dishes Ã˜ 270 mm.
- Wash cycles: 90" - 120" - 180".
- Electronic control. Digital displays.
- Selector for an optional cold rinse at the end of the cycle.
- Made of stainless steel.
- The door has double skin.
- Double rotating wash and rinse systems, above and below, made of stainlessÂ steel.
- Wash pump: 260 W.
- Drain pump: 30 W. Drainage cycle.
- Tank with 2.0 kW heating element.
- Tank capacity: 13 litres.
- Boiler with 2.8 kW heating element.
- Boiler capacity: 4 litres.
- Water consumption: 2.4 liters/rinse.
- Thermostatic temperature control: washing at 60 ÂºC and rinsing at 90 ÂºC.
- Security thermostats.
- Built-in automatic rinse dispenser and detergent doser.
- Built-in non-return valve.
- Safety magnetic switch for door opening.
- Adjustable legs.
- WaterMark approved

## Description

**Fagor EVO-CONCEPT glass washer with drain pump and detergent & rinse dispenser cold rinse - CO-402BDD**

E-VO CONCEPT glass washer with 350x350 mm basket (CO-352) and 400x400 mm basket (CO-402) with double wall rigid door. Dish service height up to 220 mm (CO-352) and 270 mm (CO-402). Constant water consumption of 2 liters per cycle for the rinse with a mains pressure of 2 bar. New optimized hydraulic EFFI-WASH system, with stainless steel wash arms and 0.26 kW pump, guaranteeing a top quality effective, and efficient wash with an optimum Sinner circle balance. It also has a built-in rinse aid

dispenser drainage pump (B) and detergent dispenser (DD) fitted at the factory or supplied in kit form It has adjustable feet to permit leveling according to the needs of the establishment. Magnetic door open sensor. Electronical control panel making it easy to use.

## Key Features

- Front loading glasswasher - EVO Generation - Advanced range.
- Basket size: 400 x 400 mm.
- Hourly production: 40 baskets/hour.
- Clearance (max ware height): 275 mm.
- Valid for dishes Ø 270 mm.
- Wash cycles: 90" - 120" - 180".
- Electronic control. Digital displays.
- Selector for an optional cold rinse at the end of the cycle.
- Made of stainless steel.
- The door has double skin.
- Double rotating wash and rinse systems, above and below, made of stainless steel.
- Wash pump: 260 W.
- Drain pump: 30 W. Drainage cycle.
- Tank with 2.0 kW heating element.
- Tank capacity: 13 litres.
- Boiler with 2.8 kW heating element.
- Boiler capacity: 4 litres.
- Water consumption: 2.4 liters/rinse.
- Thermostatic temperature control: washing at 60 ºC and rinsing at 90 ºC.
- Security thermostats.
- Built-in automatic rinse dispenser and detergent doser.
- Built-in non-return valve.
- Safety magnetic switch for door opening.
- Adjustable legs.
- WaterMark approved

## Additional Information

- Total power: 3.06 kW.
- Dimensions: 470 x 520 x 720 mm.
- Equipment: one basket 400x400, one supplement for dishes and one cutlery container.

**Certified Product**

**2 Years Parts and Labour Warranty**

## Your Shipping Specifications

| | |
|---|---|
| **Net Weight (Kg)** | 36 |
| **Width (mm)** | 470 |
| **Depth (mm)** | 520 |
| **Height (mm)** | 720 |
| **Packing Width (mm)** | 530 |
| **Packing Depth (mm)** | 680 |
| **Packing Height (mm)** | 890 |
| **Power** | 11.02 MJ |
| **Warranty** | 2 Years Parts and Labour |