BENCHFOODS

28 TRAY / 11.9 M² TRAY AREA
COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL





Uniform Drying Without Rotation

Completion Cooling Cycle

Time and Temp Memory Function

199 Hour Timer

Ambient - 90°C Precision Thermostats

Quiet Operation

Ambient Air Mode

Food-Grade 304 Stainless Steel

28CUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	6.8 kW (3.75 kw x 2 Zones)	**Number of Racks**	4
Avg Power Usage	3.4 kW (1.7 kW x 2 Zones)	**Number of Butcher Hooks**	240
Voltage / Frequency	220-240V/50-60Hz	**Total Tray Area**	11.9 m^2
Max Amperage	29A	**Total Trays**	28
Safety Breaker Required	Single Phase/32A	**Tray Dimensions**	50 x 85 cm
Temperature Range	15°C - 90°C (1°C Increments), plus Ambient Air Mode	**Space Between Trays**	50 mm
Timer	0 - 199hr	**Tray Mesh Spacing**	12 x 12 mm
Independent Zones	2	**Machine Weight**	119 kg
Average Noise Level	60 dB	**Product Dimensions (W x H x D)**	880 x 1690 x 670 mm
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		
Certifications	ANSI/NSF4, UL/cUL, RCM, AS/NZS 4417, CE, UKCA		