BENCHFOODS

16 TRAY / 2.56 M² TRAY AREA
COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL





Uniform Drying Without Rotation

Completion Cooling Cycle

Time and Temp Memory Function

199 Hour Timer

Ambient - 90°C Precision Thermostats

Quiet Operation

Ambient Air Mode

Food-Grade 304 Stainless Steel

16CUDG - BILTONG BUNDLE SPECIFICATIONS

Max Power Usage	1.5 kW	**Number of Racks**	2
Avg Power Usage	750 W	**Number of Butcher Hooks**	60
Voltage / Frequency	220-240V/50-60Hz	**Total Tray Area**	2.56 m²
Max Amperage	8A	**Total Trays**	16
Safety Breaker Required	Single Phase/10A (Standard Household Outlet)	**Tray Dimensions**	40 x 40 cm
Temperature Range	15°C - 90°C (1°C Increments), plus Ambient Air Mode	**Space Between Trays**	35 mm
Timer	0 - 199hr	**Tray Mesh Spacing**	8 x 8 mm
Independent Zones	1	**Machine Weight**	30kg
Average Noise Level	40 dB (Quiet)	**Product Dimensions (W x H x D)**	470 x 730 x 575 mm
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminium door handle; Tempered glass observation window; Control Panel with PVC finish.		
Certifications	ANSI/NSF4, UL/cUL, RCM, AS/NZS 4417, CE, UKCA		